



Residential All-in-one
Heat Pump Water Heater



Mitsubishi
Compressor



LED
Touch Screen



High
Temperature



Anti-corrosion
Water Tank

| Model | | NE-F20HWR2-200L | NE-F25HWR2-250L | NE-F30HWR2-300L |
|--|-----------------------|----------------------|----------------------|----------------------|
| Energy Efficiency Rating | / | A+ | A+ | A+ |
| DB/WB: 20°C/15°C; heating water from 15°C to 55°C | Heating Capacity(kW) | 1.8 | 2.42 | 2.42 |
| | Rated Power Input(kW) | 0.47 | 0.62 | 0.62 |
| | COP(W/W) | 3.82 | 3.88 | 3.88 |
| Hot Water Volume | L/h | 39 | 52 | 52 |
| Water Tank Volume | L | 200 | 250 | 300 |
| Max. Power Input | kW | 2.69 | 2.93 | 2.93 |
| Max. Running Current | A | 12.2 | 13.4 | 13.4 |
| Power Supply | V/Ph/Hz | 220-240V-50Hz | 220-240V-50Hz | 220-240V-50Hz |
| Wi-Fi Function | / | YES | YES | YES |
| Electric Heating | kW | 2.0 | 2.0 | 2.0 |
| Max.Outlet Water Temperature | °C | 75 | 75 | 75 |
| Refrigerant | / | R134a | R134a | R134a |
| Water Tank Type | / | Enamel | Enamel | Enamel |
| Compressor | / | GMCC | Panasonic | Panasonic |
| Gas Control | / | EEV | EEV | EEV |
| Ambient Temperature | °C | -7 - 43 | -7 - 43 | -7 - 43 |
| Power Cord Specifications | / | 3*1.5mm ² | 3*2.5mm ² | 3*2.5mm ² |
| Water Connection | / | G1/2"(female) | G3/4"(female) | G3/4"(female) |
| Product Dimensions | mm | Ø570 * 1800 | Ø640 * 1802 | Ø640 * 2020 |
| Packing Dimensions | mm | 645×645×1970 | 740×740×1920 | 740×740×2140 |
| Net Weight | kg | 96 | 123 | 141 |
| Water Proof Level | / | IPX4 | IPX4 | IPX4 |
| Noise Level | dB(A) | ≤52 | ≤53 | ≤53 |