GENERAL HT500 SET

SMART DIGITAL ROOM THERMOSTAT (Wi-Fi)

PRECIO DE LISTA: ----- U\$S 190 + IVA







- > Temperature adjustment via room thermostat
- > Digital LCD display with backlight
- > Touch buttons
- > Outside temperature indicator, Battery indicator
- > Daily and Weekly Program
- > Smart or normal wireless room thermostat

6 Different Modes Options

















Control your house temperature with location mode







With location mode, you can lower the temperature of your house when you move away or increase the temperature when you get close.

SUPPLY VOLTAGE (USAGE WITH ADAPTER)	5V (DC)
SUPPLY VOLTAGE (USAGE WITH BATTERY)	3V DC (2 X AAA Alkaline Battery)
MAX, LOAD CURRENT (USAGE WITH ADAPTER)	500 mA
MAX. LOAD CURRENT (USAGE WITH BATTERY)	80 mA
DIMENSIONS	131mm / 74mm / 25.5mm
TEMPERATURE MEASUREMENT SENSITIVITY	0.1°C
TEMPERATURE SETTING RANGE	0.1°C - 1.0°C
OPERATING SENSITIVITY	0.5°C
WI-FI CONNECTION FREQUENCY	WFFI 802.11 b/g/n @ 2.4Ghz
COMMUNICATION DISTANCE	100m (open area)
OPERATING TEMPERATURE	(-10°C) - (+50°C)
STORAGE TEMPERATURE	(-20°C) - (+60°C)

RECE	TECHN	ICAL	DATA	

	1	
SUPPLY VOLTAGE	220V (AC)	
DIMENSIONS	85mm / 90mm / 28.5mm	
RELAY COM-NO SWITCHING CURRENT	7A (220VAC)	
OPERATING TEMPERATURE	(-10°C) - (+50°C)	
STORAGE TEMPERATURE	(-20°C) - (+60°C)	



Control with Mobile App

You can control your house temperature whereever you are in the world with your smart room thermostat.



HT300

WIRED ROOM THERMOSTAT

PRECIO DE LISTA: ----- U\$S 80 + IVA

- > Large LCD with Backlight
- > Touch Display
- > Battery Indicator, Key Lock
- > Daily and Weekly Program
- > Comfort, Economy and Holiday Mode
- > Precise Temperature Measurement
- > Calibration



GENERAL Life Room Thermostats ensure a comfortable life by controlling your living space temperature.

You may increase your savings and your comfort level just by setting your device on daily or weekly program for heating.



ROOM THERMOSTAT TECHNICAL DATA

	OPERATING CURRENT	3V DC (2 x AAA Alkaline Battery)
	DIMENSIONS	84mm / 118mm / 24mm
	RELAY COM-NO SWITCHING CURRENT	2A (30V DC)
	TEMPERATURE MEASUREMENT ACCURACY	0.1°C
	OPERATING SENSITIVITY	0.5°C
17	SET TEMPERATURE RANGE	(5°C) – (30°C)
	BATTERY LIFE	1 Year (2 x AAA)
	OPERATING TEMPERATURE	(-10°C) (+50°C)
	STORAGE TEMPERATURE	(-20°C) - (+60°C)

CE RoHS Turkey

HT300 SET

WIRELESS ROOM THERMOSTAT

PRECIO DE LISTA: ----- U\$S 120 + IVA

- > Large LCD with Backlight
- > Touch Display
- > Battery Indicator, Key Lock
- > Daily and Weekly Program
- > Comfort, Economy and Holiday Mode
- > Precise Temperature Measurement
- > Calibration



CE RED RoHS

ROOM THERMOSTAT TECHNICAL DATA

			the potential.
OPERATING CURRENT	3V DC (2 x AAA Alkaline Battery)	OPERATING TEMPERATURE RANGE	(5°C) - (30°C)
DIMENSIONS	84mm / 118mm / 24mm	BATTERY LIFE	1 Year (2 x AAA)
TEMPERATURE MEASUREMENT ACCURACY	0.1°C	OPERATING TEMPERATURE	(-10°C) - (+50°C)
OPERATING SENSITIVITY	0.5°C	STORAGE TEMPERATURE	(-20°C) - (+60°C)

RECEIVER TECHNICAL DATA

SUPPLY VOLTAGE	220V (AC)
DIMENSIONS	85mm / 90mm / 28.5mm
RELAY COM-NO SWITCHING CURRENT	7A (220VAC)
STORAGE TEMPERATURE	(-20°C) - (+60°C)



llife.com.tr generallife.com.tr

HT250S

WIRED ROOM THERMOSTAT

PRECIO DE LISTA: ----- U\$S 50 + IVA

- > Large LCD with Backlight
- > Digital Room Thermostat
- > Battery Indicator
- > Easy Usage
- > Precise Temperature Measurement
- > On-Off Control
- > Calibration



 $\label{eq:general-conformal-confor$

Your room thermostat provides both comfort and savings by keeping the temperature of your home constant at the temperature you set.



ROOM THERMOSTAT TECHNICAL DATA

OPERATING CURRENT	3V DC (2 x AAA Alkaline Battery)
DIMENSIONS	88mm / 136mm / 34mm
RELAY COM-NO SWITCHING CURRENT	2A (30V DC)
TEMPERATURE MEASUREMENT ACCURACY	0.1°C
OPERATING SENSITIVITY	0.5°C
SET TEMPERATURE RANGE	(5°C) - (30°C)
BATTERY LIFE	1 Year (2 x AAA)
OPERATING TEMPERATURE	(-10°C) - (+50°C)
OTOBAGE TEMPERATURE	(0000) (.0000)

CE RoHS Turkey



HT250S SET

WIRELESS ROOM THERMOSTAT

PRECIO DE LISTA: ----- U\$S 100 + IVA

- > Large LCD with Backlight
- > Digital Room Thermostat
- > Battery Indicator
- > Easy Usage
- > Precise Temperature Measurement
- > On-Off Control
- > Calibration



PGENERAL

23.5

ROOM THERMOSTAT TECHNICAL DATA

			the potential.
OPERATING CURRENT	3V DC (2 x AAA Alkaline Battery)	OPERATING TEMPERATURE RANGE	(5°C) - (30°C)
DIMENSIONS	88mm / 136mm / 34mm	BATTERY LIFE	1 Year (2 x AAA)
TEMPERATURE MEASUREMENT ACCURACY	0.1°C	OPERATING TEMPERATURE	(-10°C) - (+50°C)
OPERATING SENSITIVITY	0.5°C	STORAGE TEMPERATURE	(-20°C) - (+60°C)

RECEIVER TECHNICAL DATA

SUPPLY VOLTAGE	220V (AC)
DIMENSIONS	85mm / 90mm / 28.5mm
RELAY COM-NO SWITCHING CURRENT	7A (220VAC)
STORAGE TEMPERATURE	(-20°C) - (+60°C)



generallife.com.tr generallife.com.tr

HT120

WIRED ROOM THERMOSTAT

PRECIO DE LISTA: ----- U\$S 35 + IVA

- > Digital LCD Display
- > Easy Usage
- > Precise Temperature Measurement
- > On-Off Control
- > Calibration



GENERAL Life Room Thermostats ensure a comfortable life by controlling your living space temperature.

Your room thermostat provides both comfort and savings by keeping the temperature of your home constant at the temperature you set.



ROOM THERMOSTAT TECHNICAL DATA

OPERATING CURRENT	3V DC (2 x AAA Alkaline Battery)
DIMENSIONS	80mm / 80mm / 35mm
RELAY COM-NO SWITCHING CURRENT	2A (30V DC)
TEMPERATURE MEASUREMENT ACCURACY	0.1°C
OPERATING SENSITIVITY	0.5°C
SET TEMPERATURE RANGE	(5°C) – (30°C)
BATTERY LIFE	1 Year (2 x AAA)
OPERATING TEMPERATURE	(-10°C) = (+50°C)
STORAGE TEMPERATURE	(-20°C) - (+60°C)

CE RoHS



HT120 SET

WIRELESS ROOM THERMOSTAT

PRECIO DE LISTA: ----- U\$S 80 + IVA

- > Digital LCD Display
- > Easy Usage
- > Precise Temperature Measurement
- > On-Off Control
- > Calibration



C€ RED RoHS

Turkey

			the potential.
OPERATING CURRENT	3V DC (2 x AAA Alkaline Battery)	OPERATING TEMPERATURE RANGE	(5°C) - (30°C)
DIMENSIONS	80mm / 80mm / 30mm	BATTERY LIFE	1 Year (2 x AAA)
TEMPERATURE MEASUREMENT ACCURACY	0.1°C	OPERATING TEMPERATURE	(-10°C) — (+50°C)
OPERATING SENSITIVITY	0.5°C	STORAGE TEMPERATURE	(-20°C) - (+60°C)

RECEIVER TECHNICAL DATA

SUPPLY VOLTAGE	220V (AC)
DIMENSIONS	85mm / 90mm / 28.5mm
RELAY COM-NO SWITCHING CURRENT	7A (220VAC)
STORAGE TEMPERATURE	(-20°C) (+60°C)



generallife.com.tr generallife.com.tr

FC100

DIGITAL FANCOIL THERMOSTAT

MODELO NO DISPONIBLE

- > For 2 pipe fan coil systems
- > Manual heating and cooling option
- > User Friendly Interface
- > 3 Stage Fan Speed



 $\textbf{GENERAL Life} \ Fan \ Coil \ Thermostats \ ensure \ a \ comfortable \ life \ by \ controlling \ your \ living \ space temperature.$

FC100 is a digital fan coil thermostat. The user can adjust the Fan Coil Thermostat with the required temperature and fan speed to get more comfortable and economic heating/cooling.



FAN COIL THERMOSTAT TECHNICAL DATA

OPERATING CURRENT	110-220V AC 50/60 Hz
DIMENSIONS	90mm / 145mm / 29.8mm
RELAY NO SWITCHING CURRENT	8A (250VAC - Resistive Load)
	8A (30VDC - Resistive Load)
TEMPERATURE MEASUREMENT ACCURACY	0.1°C
OPERATING SENSITIVITY	0.5°C
OPERATING TEMPERATURE RANGE	(5°C) - (35°C)
OPERATING TEMPERATURE	(-10°C) - (+50°C)
STORAGE TEMPERATURE	(-20°C) - (+60°C)

CE RoHS



FC220

DIGITAL FANCOIL THERMOSTAT

PRECIO DE LISTA: ----- U\$S 60 + IVA

- > For 2 pipe fan coil systems
- > Manual heating and cooling option
- > User Friendly Interface
- > Large LCD Display & Backlight
- > Touch Buttons





AN COIL THERMOSTAT TECHNICAL DATA

OPERATING CURRENT	110-220V AC 50/60 Hz
DIMENSIONS	90mm / 145mm / 27mm
RELAY NO SWITCHING CURRENT	5A (277VAC - Resistive Load)
	3A (30VDC - Resistive Load)
TEMPERATURE MEASUREMENT ACCURACY	0.1°C
OPERATING SENSITIVITY	0.5°C
OPERATING TEMPERATURE RANGE	(5°C) - (35°C)
OPERATING TEMPERATURE	(-10°C) - (+50°C)
STORAGE TEMPERATURE	(-20°C) - (+60°C)

C€ RoHS

generallife.com.tr generallife.com.tr