



Figura similar

Ficha técnica

Datos técnicos

Presión de entrada máx.	6 bar
-------------------------	-------

Conexión de tubería

Conexión entrada	DN 40
Conexión de salida	DN 40
Conexión de la bomba	DN 40
Tubería	DN 40
Presión nominal	PN 6

Materiales

Material	Acero inoxidable
Material	Acero

Información de pedido

Datos del producto

Marca	Wilo
Denominación del producto	Juego de contrabridas DN 40, PN 6
Referencia	2105578
Número EAN	4048482089430
Color	gris
Cantidad mínima de pedido	1
Disponibilidad en el mercado	2014-03-01

Medidas y pesos

Longitud con embalaje	215 mm
Longitud <i>L</i>	130 mm
Altura con embalaje	100 mm
Altura <i>H</i>	38 mm
Ancho con embalaje	195 mm
Ancho <i>W</i>	130 mm
Peso bruto aproximado <i>m</i>	3,4 kg
Peso neto aproximado <i>m</i>	3,1 kg

Embalaje

Tipo de embalaje	Caja de cartón
Propiedades del embalaje	Embalaje de transporte
Número por palé	50
Número por capa	20

Texto de especificación

Two steel weld neck flanges in accordance with DIN-EN 1092-1 type 11 with a neck for welding to pipes as well as gaskets and screws/nuts for the flange connections.

Depending on the configuration of the operating pressure of an installation, the appropriate counter flange must be selected for the operating pressure.

Scope of delivery

- > 2 weld neck flanges
- > 2 gaskets
- > Screws/nuts (number and size based on flange version)

Datos técnicos

Conexión entrada	DN 40
Conexión de salida	DN 40
Presión nominal	PN 6
Material	Acero inoxidable
Peso	3,1 kg
Marca	Wilo
Ref.	2105578